



GEGEVENS	DATA	DONNEES	
Max. Statische last	Max. Static load	Charge statique maxi	kg. 4200
Verhouding	Ratios	Rapports	1/61 1/49 1/39 2/53 3/47
Vermogen gamma Bij 4/16 polen	Powers range At 4/16 poles	Gamme puissances 4/16 pôles	3.5 - 11 kW SYNC
Vermogen gamma Bij 6/24 polen	Powers range At 6/24 poles	Gamme puissances 6/24 pôles	2.9 - 6.6 kW SYNC
Vermogen gamma VVVF bij 4 polen	Powers range VVVF at 4 poles	Gamme puissances VVVF 4 pôles	3.3 - 20.6 kW SYNC
Vermogen gamma VF S/D motor	Powers range VF S/D motor	Gammes puissances Moteur VF S/D	1.5 - 5.9 kW SYNC
Inertiemoment J	Moment of inertia J	Moment d'inertie J	Kgm ² 0.026
Levenslange olie	Lubricated for life	Lubrifié à vie	-----

	GEWICHTSTABEL zonder vliegwiel en traktieschijf	WEIGHT TABLE without fly-wheel and sheave	TABELLE DES POIDS sans Volant et poulie
4/16	kW 3.5 - 4.0 kg 274 kW 9.2 kg 317	kW 4.9 kg 279 kW 11 kg 327	kW 5.5 kg 285 kW 6.0 - 7.3 kg 297
6/24	kW 2.9 - 3.3 kg 288 kW 5.9 - 6.6 kg 330	kW 3.7 - 4.0 kg 300 kW 4.4 kg 305	kW 4.9 - 5.5 kg. 320
VVVF	kW 3.3 - 5.9 kg 274 kW 13.6- 17.6 kg 317	kW 6.3 - 7.3 kg 279 kW 18 - 20.6 kg 327	kW 7.7 - 11 kg 285 kW 11.4- 13.2 kg 297